



actual size

# SMD Quartz Crystal · JXS32

- 4 pad version, 3.2 x 2.5 mm
- seam sealed ceramic/metal package
- extended temperature ranges available
- high mechanical reliability type available
- for automotive type, see automotive datasheet



RoHS compliant



Pb free



REACH compliant



Conflict mineral free

## GENERAL DATA

TYPE	JXS32
frequency range	8.0 ~ 54.0 MHz (fund. AT-cut)
frequency tolerance at 25 °C	± 10 ppm / ± 30 ppm
load capacitance $C_L$	8/12 pF standard (option: 6 pF ~ 30 pF / series)
shunt capacitance $C_0$	< 5 pF
storage temperature	-40 °C ~ +125 °C
drive level max.	100 µW
shock resistance	> 100 g (half sine pulse, 6.0 ms)
aging	< ± 3 ppm first year (option: < ± 1 ppm first year for tol. ± 10 ppm)

\* lower ESR options case-by-case, ask for availability

## ESR (SERIES RESISTANCE RS)

frequency in MHz	vibration mode	ESR max. in Ω	ESR typ. in Ω
8.0	fund. - AT	300 / 200*	200 / 150*
8.1 ~ 9.999	fund. - AT	400 / 300*	250 / 200*
10.0 ~ 11.999	fund. - AT	300	150
12.0 ~ 12.999	fund. - AT	100	50
13.0 ~ 15.999	fund. - AT	100	40
16.0 ~ 18.999	fund. - AT	80	40
19.0 ~ 21.999	fund. - AT	60	30
22.0 ~ 29.999	fund. - AT	50	25
30.0 ~ 54.000	fund. - AT	50	20

## TABLE 1: FREQUENCY STABILITY VS. TEMPERATURE

		± 10 ppm	±15 ppm	±20 ppm	±30 ppm	±50 ppm	±100 ppm
-20 °C ~ +70 °C	STD.	○	○	○	○	○	○
-30 °C ~ +85 °C	T(-30/+85)	○	○				
-40 °C ~ +85 °C	T1		○	○	○	○	○
-40 °C ~ +105 °C	T2			○	○	○	○
-40 °C ~ +125 °C	T3					○	○

○ available


## MARKING

frequency with load capacitance code  
company code / date code / internal code


date code: year/month; A ~ M: Jan. - Dec.; example: 3A = 2023 January  
3: 2023 4: 2024 5: 2025 6: 2026 7: 2027 8: 2028

Jan.	Febr.	Mar.	Apr.	May	June
A	B	C	D	E	F
July	Aug.	Sept.	Oct.	Nov.	Dec.
G	H	J	K	L	M


## DIMENSIONS




top view




side view



bottom view



#2-#4: connected to lid, preferably connect to GND crystal connection



pad layout

in mm



## ORDER INFORMATION

Q	frequency	type	load capacitance	tolerance at 25 °C	stability vs. temp. range	option
Quartz	8.0 ~ 54.0 MHz	JXS32	8/12 pF standard 6 pF ~ 30 pF available S for series	10 = ± 10 ppm 30 = ± 30 ppm	10 = ± 10 ppm 15 = ± 15 ppm 20 = ± 20 ppm 30 = ± 30 ppm 50 = ± 50 ppm 100 = ± 100 ppm	blank = -20 °C ~ +70 °C T(-30/+85) = -30 °C ~ +85 °C T1 = -40 °C ~ +85 °C T2 = -40 °C ~ +105 °C T3 = -40 °C ~ +125 °C FU = for fundamental frequencies ≥ 20 MHz HMR = high mechanical reliability (3000g/half sine wave/0.3ms)


**Example: Q 24.0-JXS32-12-30/30-T1-FU-LF** (Suffix LF = RoHS compliant / Pb free)

# SMD Quartz Crystal · JXS32

## TAPING SPECIFICATION



## REFLOW SOLDERING PROFILE



note: parts are also suitable for soldering systems with lead (Pb) content

## LOAD CAPACITANCE CODES

6 pF: q	12 pF: a	18 pF: f	27 pF: h
7 pF: m	13 pF: v	20 pF: c	30 pF: .
8 pF: k	14 pF: x	22 pF: g	series: s
9 pF: n	15 pF: j	24 pF: d	
10 pF: h	16 pF: b	25 pF: r	
11 pF: l	17 pF: t		

example 20.0 MHz / 12 pF: 20a00